

NOW AVAILABLE!

EVERCONNECT™

14N SERIES

NSF APPROVED NO-HUB COUPLINGS

CERTIFIED TO CISPI 310 & CSA B602 STANDARDS



EVERCONNECT 14N Series NSF approved no-hub couplings are manufactured using 304 series stainless steel bands attach to corrugated pattern stainless steel shield over molded one-piece elastomer sealing gasket. They provide the perfect fit for joining hub-less cast iron soil pipe and fittings in drain waste & vent applications. Longer slots on clamping band provide greater adaptability to varying cast iron pipe diameters. Lightweight and easy to install, by tightening worm screw to 60 inch lbs. torque. 14N Series couplings are tested and certified to ASTM C1277, NSF certified to CISPI 310 and CSA B602 standards, and certified to CAN/ULC S102.2-07

Specifications:

- 304 Series stainless steel bands
- NSF Certified to CISPI 310 CSA B602
- Certified by Intertek to CAN/ULC S102.2-07
- Tested and Certified to ASTM C1277
- Elastomeric Gasket conforms to ASTM C-564
- Maintains 4.3 PSI Water Pressure
- Tighten with 5/16" Hex Driver to 60 in-lbs. torque



PART #	SIZE	DESCRIPTION	PACKING	LIST
14112N	1-1/2"	NSF No-Hub Coupling	100	\$3.35
14200N	2"	NSF No-Hub Coupling	100	\$3.35
14300N	3"	NSF No-Hub Coupling	100	\$4.76
14400N	4"	NSF No-Hub Coupling	100	\$5.19
14500N	5"	NSF No-Hub Coupling	20	\$12.65
14600N	6"	NSF No-Hub Coupling	25	\$14.33
14800N	8"	NSF No-Hub Coupling	15	\$25.20

Materials / Dimensional Data

SIZE	SHIELD WIDTH	TORQUE (IN-LBS)	NO. OF CLAMPS	CLAMP WIDTH
1-1/2"	2-1/8"	60 in-lbs	2	9/16"
2"	2-1/8"	60 in-lbs	2	9/16"
3"	2-1/8"	60 in-lbs	2	9/16"
4"	2-1/8"	60 in-lbs	2	9/16"
5"	3"	60 in-lbs	4	9/16"
6"	3"	60 in-lbs	4	9/16"
8"	4"	60 in-lbs	4	9/16"

	MATERIAL
Band	SS304 Stainless Steel
Screw	5/16" Hex head made of SS304 Stainless Steel
Housing	SS304 Stainless Steel
Shield	0.007" Thick corrugated design SS301 Stainless Steel
Gasket	Elastomeric Compound Conforming to ASTM C 564